

RANGE DESIGN

Trico 2000

Flexible PVC hose for water transport at medium pressures and frequent use

Insert in range Design, Trico 2000 is an excellent flexible PVC garden hose with three layers, with a good distribution one wall thickness of layers, which makes it suitable for frequent use at medium pressure.



Ø _{int} (mm)	Ø _{ext} (mm)	Weight (g/m)	Bursting pressure (bar)	Length (m)	Resistance to traction
12,5 (1/2")	16,9 ± 0.5	125	17	50	
15 (5/8")	20,3 ± 0.5	180	17	15 25 50	Tensile strength: ≥ 5 MPa Elongation at break: ≥ 150 %
19 (3/4")	25,3 ± 0.5	270	17	25 50	Adhesion: ≥ 12 N/cm
25 (1")	31,9 ± 0.5	380	17	25 50	

Distribution of the 3 layers:

1. PVC layer flexible, white.
2. Knitted layer with high resistance polyester yarn, white.
3. PVC layer flexible, crystal blue.

Other characteristics

Material: Plasticized poly (vinyl chloride), plasticizers and other additives necessary to facilitate the production. The material used does not contain lead, cadmium or barium.

Technical:



Use:



Used frequently in conducting water at medium pressures for use in gardening, for domestic use at a recommended temperature of -10°C/+60°C.

Remarks for use:

The recommend fittings for this hose are the plastic click fitting in colour grey/grey. Easy cut with a knife or scissors. For a good performance, it should be avoid trampling the hose, especially with machines or heavy equipment. To increase the durability, the hose should be wrapped and kept clean without water after each use.



- 1 Spray Nozzle Click
- 2 Hose connector Click
- 1 Tap Adaptor Click

The information and data assume is accurate and reliable.

The characteristics can be improved as a result of technological advances and improvements.

Our Quality Department is at your disposal for any clarification.

IBOTEC.
HIGH TECH PIPES

Apartado 2037 . 3701-906 Cesar – Portugal
Tel.: +351 256 850 130 – Fax: +351 256 850 139
ibotec@ibotec.pt – www.ibotec.pt